



NINGBO HIGHLITE ILLUMINATION CO., LTD.

CE LVD REPORT

Prepared For:	NINGBO HIGHLITE ILLUMINATION CO., LTD. Room 2202, 22F, Bank of China Mansion, Commercial Center NO. 318, He Yuan Road, Yinzhou Dist., Ningbo, 315000, China
Product Name:	TRANSCEND 500 RC HEADLAMP
Trade Name:	NEBO
Main Test Model	7005
Additional Model:	7003,7004,NEB-HLP-0004
Prepared By :	BST Testing (Shenzhen) Co., Ltd.
	No.7,New Era Industrial Zone, Guantian, Bao'an District, Shenzhen, Guangdong, China
Test Date:	Jul.04, 2020 - Jul.16, 2020
Date of Report :	Jul.16, 2020
Report No.:	BSTXD200710682201SR

**TEST REPORT****EN 60598-2-4****Luminaires****Part 2: Particular Requirements****Section Four – Portable general purpose luminaires**

Testing Laboratory Name	BST Testing (Shenzhen) Co., Ltd.
Address	No.7, New Era Industrial Zone, Guantian, Bao'an District, Shenzhen, Guangdong, China
Testing location	BST Testing (Shenzhen) Co., Ltd.
Applicant's Name	NINGBO HIGHLITE ILLUMINATION CO., LTD.
Address	Room 2202, 22F, Bank of China Mansion, Commercial Center NO. 318, He Yuan Road, Yinzhou Dist., Ningbo, 315000, China
Manufacturer	NINGBO HIGHLITE ILLUMINATION CO., LTD.
Address	Room 2202, 22F, Bank of China Mansion, Commercial Center NO. 318, He Yuan Road, Yinzhou Dist., Ningbo, 315000, China
Test specification	
Standard	EN 60598-2-4:2018 EN 60598-1:2015+A1:2018
Procedure deviation	N/A
Non-standard test method	N/A
Test item description	See page 1
Trade Name	See page 1
Model and/or type reference	See page 1
Rating(s)	See label
Test case verdicts:	
Test case does not apply to the test object	N(/A)
Test item does meet the requirement	P(ass)
Test item does not meet the requirement	F(ail)



General remarks:

This report shall not be reproduced except in full without the written approval of the testing laboratory.

The test results presented in this report relate only to the item(s) tested.

"(see remark #)" refers to a remark appended to the report.

"(see Annex #)" refers to an annex appended to the report.

General product information:

Note: The series products have the same circuit diagram, PCB layout and functionality. The differences are the model name, so, we select 7005 to test.

Copy of marking plate:

TRANSCEND 500 RC HEADLAMP

Model: 7005

Rated: 3.7V, 5.18W



NINGBO HIGHLITE ILLUMINATION CO., LTD.

Prepared by :

Celine Zhao

Engineer

Reviewer :

Jacky Zhang

Supervisor

Approved & Authorized Signer :



Manager



EN 60598-2-4			
Clause	Requirement + Test	Result - Remark	Verdict
4.4 (0)	GENERAL TEST REQUIREMENTS		P
4.4 (0.1)	Information for luminaire design considered	Yes ☒ No ☐ Lamp standard:	—
4.4(0.3)	More sections applicable	Yes ☒ No ☐ Section/s:	—
4.5 (2)	CLASSIFICATION OF LUMINAIRES		P
4.5 (2.2)	Type of protection	Class II	P
4.5 (2.3)	Degree of protection	IP20	P
4.5 (2.5)	Luminaire for normal use	Yes ☐ No ☒	—
	Luminaire for rough service	Yes ☒ No ☐	—
4.5.1 (-)	Ordinary luminaire	Yes ☒ No ☐	—
4.5.2 (-)	Portable luminaire for outdoor use	Yes ☐ No ☒	—
4.5.3 (2.4)	Luminaire suitable for direct mounting on normally flammable surfaces	Yes ☐ No ☒	—
4.6 (3)	MARKING		P
4.6 (3.2)	Mandatory markings		P
	Position of the marking	On the enclosure	P
	Format of symbols/text		P
4.6 (3.3)	Additional information		P
	Language of instructions	English	P
4.6 (3.3.1)	Combination luminaires		N
4.6 (3.3.2)	Nominal frequency in Hz		P
4.6 (3.3.3)	Operating temperature		P
4.6 (3.3.4)	Symbol or warning notice		N
4.6 (3.3.5)	Wiring diagram		N
4.6 (3.3.6)	Special conditions		N
4.6 (3.3.7)	Metal halide lamp luminaire – warning		N
4.6 (3.3.8)	Limitation for semi-luminaires		N
4.6 (3.3.9)	Power factor and supply current		N
4.6 (3.3.10)	Suitability for use indoors		P
4.6 (3.3.11)	Luminaires with remote control		N
4.6 (3.3.12)	Clip-mounted luminaire – warning		N



4.6 (3.3.13)	Specifications of protective shields		N
4.6 (3.3.14)	Symbol for nature of supply	AC	P
4.6 (3.3.15)	Rated current of socket outlet		N
4.6 (3.3.16)	Rough service luminaire		N
4.6 (3.3.17)	Mounting instruction for type Y, type Z and some type X attachments	Type Y	P
4.6 (3.3.18)	Non-ordinary luminaires with PVC cable		N
4.6 (3.3.19)	Protective conductor current in instruction if applicable		N
4.6 (3.3.20)	Provided with information if not intended to be mounted within arm's reach		P
4.6 (3.3.21)	Non replaceable and non-user replaceable light sources information provided		N
	Cautionary symbol		P
4.6 (3.3.22)	Controllable luminaires, classification of insulation provided		N
4.6 (3.4)	Test with water	15s	P
	Test with hexane	15s	P
	Legible after test	The marking is legible	P
	Label attached		P
4.6.1 (-)	Luminaire not suitable for outdoor application		
	Required symbol		
	Information in the instructions		
4.6.2 (-)	Outdoor use, socket outlet incorporated in the luminaire		
	Maximum current rating marked		
	Position of the marking		

4.7 (4)	CONSTRUCTION		P
4.7 (4.2)	Components replaceable without difficulty		P
4.7 (4.3)	Wireways smooth and free from sharp edges		P
4.7 (4.4)	Lampholders		N
4.7 (4.4.1)	Integral lampholder		N
4.7 (4.4.2)	Wiring connection		N
4.7 (4.4.3)	Lampholder for end-to-end mounting		N
4.7 (4.4.4)	Positioning		N
	- pressure test (N)		-



	After test the lampholder comply with relevant standard sheets and show no damage		N
	After test on single-capped lampholder the lampholder have not moved from its position and show no permanent deformation		N
	- bending test (N)		-
	After test the lampholder have not moved from its position and show no permanent deformation		N
4.7 (4.4.5)	Peak pulse voltage		N
4.7 (4.4.6)	Centre contact		N
4.7 (4.4.7)	Parts in rough service luminaires resistant to tracking		N
4.7 (4.4.8)	Lamp connectors		N
4.7 (4.4.9)	Caps and bases correctly used		N
4.7 (4.4.10)	Light source for lampholder or connection according IEC 60061 not connected another way		N
4.7 (4.5)	Starter holders		N
	Starter holder in luminaires other than class II		N
	Starter holder class II construction		N
4.7 (4.6)	Terminal blocks		N
	Tails		N
	Unsecured blocks		N
4.7 (4.7)	Terminals and supply connections		P
4.7 (4.7.1)	Contact to metal parts		N
4.7 (4.7.2)	Test 8 mm live conductor		N
	Test 8 mm earth conductor		N
4.7 (4.7.3)	Terminals for supply conductors		N
4.7 (4.7.3.1)	Welded method and material		N
	- stranded or solid conductor		N
	- spot welding		N
	- welding between wires		N
	- Type Z attachment		N
	- mechanical test according to 15.6.2		N
	- electrical test according to 15.6.3		N
	- heat test according to 15.6.3.2.3 and 15.6.3.2.4		N
4.7 (4.7.4)	Terminals other than supply connection		N
4.7 (4.7.5)	Heat-resistant wiring/sleeves		P
4.7 (4.7.6)	Multi-pole plug		N



	- test at 30 N		N
4.7 (4.8)	Switches		P
	- adequate rating		P
	- adequate fixing		P
	- polarized supply		P
	- compliance with IEC 61058-1 for electronic switches		P
4.7 (4.9)	Insulating lining and sleeves		N
4.7 (4.9.1)	Retainment		N
	Method of fixing		N
4.7 (4.9.2)	Insulated linings and sleeves:		N
	Resistant to a temperature > 20 °C to the wire temperature or		N
	a) & c) Insulation resistance and electric strength		N
	b) Ageing test. Temperature (°C)		N
4.7 (4.10)	Double or reinforced insulation		N
4.7 (4.10.1)	No contact, mounting surface – accessible metal parts – wiring of basic insulation		N
	Safe installation fixed luminaires		N
	Capacitors and switches		N
	Interference suppression capacitors according to IEC 60384-14		N
4.7 (4.10.2)	Assembly gaps:		N
	- not coincidental		N
	- no straight access with test probe		N
4.7 (4.10.3)	Retainment of insulation:		P
	- fixed		P
	- unable to be replaced; luminaire inoperative		N
	- sleeves retained in position		N
	- lining in lampholder		N
4.7 (4.10.4)	Protective impedance device		N
	Double or reinforced insulation bridged by appropriate and at least two resistors or two Y2 capacitors or one Y1 capacitor		N
	Y1 or Y2 capacitors comply with IEC 60384-14		N
	Resistors comply with test (a) in 14.1 of IEC 60065		N
4.7 (4.11)	Electrical connections and current-carrying parts		P



4.7 (4.11.1)	Contact pressure		P
4.7 (4.11.2)	Screws:		N
	- self-tapping screws		N
	- thread-cutting screws		N
4.7 (4.11.3)	Screw locking:		P
	- spring washer		P
	- rivets		N
4.7 (4.11.4)	Material of current-carrying parts		P
4.7 (4.11.5)	No contact to wood or mounting surface		N
4.7 (4.11.6)	Electro-mechanical contact systems		N
4.7 (4.12)	Screws and connections (mechanical) and glands		P
4.7 (4.12.1)	Screws not made of soft metal		N
	Screws of insulating material		P
	Torque test: torque (Nm); part..... :	0.5 Nm	P
	Torque test: torque (Nm); part..... :		N
	Torque test: torque (Nm); part..... :		N
4.7 (4.12.2)	Screws with diameter < 3 mm screwed into metal		N
4.7 (4.12.4)	Locked connections:		N
	- fixed arms; torque (Nm) :		N
	- lampholder; torque (Nm) :		N
	- push-button switches; torque 0,8 Nm..... :		N
4.7 (4.12.5)	Screwed glands; force (Nm) :		N
4.7 (4.13)	Mechanical strength		P
4.7 (4.13.1)	Impact tests:		P
	- fragile parts; energy (Nm) :		N
	- other parts; energy (Nm) :	0.35 Nm	P
	1) live parts	Not access	P
	2) linings		N
	3) protection	Continue to afford the degree of protection against ingress of dust, solid objects and moisture	P
	4) covers	No break	P
4.7 (4.13.3)	Straight test finger	Can't touch with live part with 30N	P
4.7 (4.13.4)	Rough service luminaires		N
	- IP54 or higher		N



	a) fixed		N
	b) hand-held		N
	c) delivered with a stand		N
	d) for temporary installations and suitable for mounting on a stand		N
4.7 (4.13.6)	Tumbling barrel		N
4.7 (4.14)	Suspensions, fixings and means of adjusting		P
4.7 (4.14.1)	Mechanical load:		N
	A) four times the weight		N
	B) torque 2,5 Nm		N
	C) bracket arm; bending moment (Nm)..... :		N
	D) load track-mounted luminaires		N
	E) clip-mounted luminaires, glass-shelve. Thickness (mm) :		N
	Metal rod. diameter (mm) :		N
	Fixed luminaire or independent control gear without fixing devices		N
4.7 (4.14.2)	Load to flexible cables		N
	Mass (kg) :		—
	Stress in conductors (N/mm ²) :		N
	Mass (kg) of semi-luminaire :		N
	Bending moment (Nm) of semi-luminaire :		N
4.7 (4.14.3)	Adjusting devices:		N
	- flexing test; number of cycles :		N
	- strands broken..... :		N
	- electric strength test afterwards		N
4.7 (4.14.4)	Telescopic tubes: cords not fixed to tube; no strain on conductors		N
4.7 (4.14.5)	Guide pulleys		N
4.7 (4.14.6)	Strain on socket-outlets		N
4.7 (4.15)	Flammable materials		P
	- glow-wire test 650°C :		P
	- spacing ≥30 mm		P
	- screen withstanding test of 13.3.1		N
	- screen dimensions		N
	- no fiercely burning material		N



	- thermal protection		N
	- electronic circuits exempted		N
4.7 (4.15.2)	Luminaires made of thermoplastic material with lamp control gear		N
	a) construction		N
	b) temperature sensing control		N
	c) surface temperature		N
4.7 (4.16)	Luminaires for mounting on normally flammable surfaces		P
	No lamp control gear : (compliance with Section 12)		N
4.7 (4.16.1)	Lamp control gear spacing:		N
	- spacing 35 mm		N
	- spacing 10 mm		N
4.7 (4.16.2)	Thermal protection:		N
	- in lamp control gear		N
	- external		N
	- fixed position		N
	- temperature marked lamp control gear		N
4.7 (4.16.3)	Design to satisfy the test of 12.6	(see clause 12.6)	N
4.7 (4.17)	Drain holes		N
	Clearance at least 5 mm		N
4.7 (4.18)	Resistance to corrosion		P
4.7 (4.18.1)	- rust-resistance		N
4.7 (4.18.2)	- season cracking in copper		P
4.7 (4.18.3)	- corrosion of aluminium		N
4.7 (4.19)	Ignitors compatible with ballast		N
4.7 (4.20)	Rough service vibration		N
4.7 (4.21)	Protective shield		P
4.7 (4.21.1)	Shield fitted if tungsten halogen lamps or metal halide lamps		N
	Shield of glass if tungsten halogen lamps		N
4.7 (4.21.2)	Particles from a shattering lamp not impair safety		N
4.7 (4.21.3)	No direct path		N
4.7 (4.21.4)	Impact test on shield		P
	Glow-wire test on lamp compartment..... :		P
4.7 (4.22)	Attachments to lamps not cause overheating or damage		P
4.7 (4.23)	Semi-luminaires comply Class II		N



4.7 (4.24)	Photobiological hazards		P
4.7 (4.24.1)	No excessive UV radiation if tungsten halogen lamps and metal halide lamps (Annex P)		P
4.7 (4.24.2)	Retinal blue light hazard		P
	Class of risk group assessed according to IEC/TR 62778		—
	Luminaires with E_{thr} :		N
	a) Fixed luminaires		N
	- distance x m, borderline between RG1 and RG2...:	RG0	N
	- marking and instruction according 3.2.23		N
	b) Portable and handheld luminaires		N
	- marking according 3.2.23 if RG1 exceeded at 200 mm according to IEC/TR 62778		N
	Portable luminaires for children IEC 60598-2-10 and Mains socket outlet nightlights IEC 60598-2-12 not exceed RG1 at 200 mm according to IEC/62778		N
4.7 (4.25)	Mechanical hazard		P
	No sharp point or edges		P
4.7 (4.26)	Short-circuit protection		N
4.7 (4.26.1)	Adequate means of uninsulated accessible SELV parts		P
4.7 (4.26.2)	Short-circuit test with test chain according 4.26.3		N
	Test chain not melt through		N
	Test sample not exceed values of Table 12.1 and 12.2		N
4.7 (4.27)	Terminal blocks with integrated screwless earthing contacts		N
	Test according Annex V		N
	Pull test of terminal fixing (20 N)		N
	After test, resistance < 0,05 Ω		N
	Pull test of mechanical connection (50 N)		N
	After test, resistance < 0,05 Ω		N
	Voltage drop test, resistance < 0,05 Ω		N
4.7 (4.28)	Fixing of thermal sensing control		N
	Not plug-in or easily replaceable type		N
	Reliably kept in position		N
	No adhesive fixing if UV radiations from a lamp can degrade the fixing		N
	Not outside the luminaire enclosure		N
	Test of adhesive fixing:		N



	Max. temperature on adhesive material (°C) :		—
	100 cycles between t min and t max		N
	Temperature sensing control still in position		N
4.7 (4.29)	Luminaires with non-replaceable light source		P
	Not possible to replace light source		P
	Live part not accessible after parts have been opened by hand or tools		P
4.7 (4.30)	Luminaires with non-user replaceable light source		N
	If protective cover provide protection against electric shock and marked with “caution, electric shock risk” symbol:		N
	Minimum two fixing means		N
4.7 (4.31)	Insulation between circuits		N
	Circuits insulated from LV supply fulfil requirements according 4.31.1 – 4.31.3		N
	Controllable luminaires requiring same level of insulation for all components, the insulation between control terminals and LV supply fulfil requirements according 4.31.1 – 4.31.3		N
4.7 (4.31.1)	SELV circuits		N
	Used SELV source		N
	Voltage ≤ ELV		N
	Insulating of SELV circuits from LV supply		N
	Insulating of SELV circuits from other non SELV circuits		N
	Insulating of SELV circuits from FELV		N
	Insulating of SELV circuits from other SELV circuits		N
	SELV circuits insulated from accessible parts according Table X.1		N
	Plugs not able to enter socket-outlets of other voltage systems		N
	Socket outlets does not admit plugs of other voltage systems		N
	Plugs and socket-outlets does not have protective conductor contact		N
4.7 (4.31.2)	FELV circuits		N
	Used FELV source		N
	Voltage ≤ ELV		N
	Insulating of FELV circuits from LV supply		N



	FELV circuits insulated from accessible parts according Table X.1		N
	Plugs not able to enter socket-outlets of other voltage systems		N
	Socket outlets does not admit plugs of other voltage systems		N
	Socket-outlets does not have protective conductor contact		N
4.7 (4.31.3)	Other circuits		N
	Other circuits insulated from accessible parts according Table X.1		N
	Class II construction with equipotential bonding for protection against indirect contacts with live parts:		N
	- conductive parts are connected together		N
	- test according 7.2.3		N
	- conductive part not cause an electric shock in case of an insulation fault		N
	- equipotential bonding in master/slave applications		N
	- master luminaire provided with terminal for accessible conductive parts of slave luminaires		N
	- slave luminaire constructed as class I		N
4.7 (4.32)	Overvoltage protective devices		N
	Comply with IEC 61643-11		N
	External to controlgear and connected to earth:		N
	- only in fixed luminaires		N
	- only connected to protective earth		N
4.7.1 (-)	Insulation not damaged when placing on support		
4.7.2 (-)	Wiring fixed, to avoid rubbing		
4.7.3 (-)	Luminaire not overturn at angle 6°		
	Outdoor use luminaire not overturn at an angle 15°		
4.7.4 (-)	Candlestick luminaires with E5 or E10 lampholders provided with a switch		
	Switch part of the luminaire or within 300 mm of the luminaire if with cord		
4.7.5 (-)	Voltage not exceed 25 V for E5 lampholders		
	E10 lampholder voltage not exceed:		
	60 V for series connection) or		
	250 V for parallel connections		
	Maximum rated wattage not exceed 100 W		



4.7.6 (-)	Portable luminaires for outdoor use tails not provided		
4.7.7 (-)	Portable luminaires for outdoor use, cable entries		
4.7.8 (-)	Portable luminaires for outdoor use, socket-outlet degree of protection at least IPX4.		
	Degree of protection maintained with or without a plug inserted into the socket-outlet.		
	Class II luminaires, mains socket-outlets, connection only to Class II luminaires.		
	Class I luminaires, mains socket-outlets, connection only to Class I luminaires.		
4.7.9 (-)	Portable luminaires for outdoor use, lampholders and plugs are of material resistant to tracking		
	Compliance to clause 13.4		

4.8 (11)	CREEPAGE DISTANCES AND CLEARANCES		P
4.8 (11.2)	Creepage distances and clearances..... :	See Table 4.7 (11.2)	—
	Impulse withstand category (Normal category II) (Category III Annex U, Table U.1)	Category II ☐ Category III ☐	—

4.9 (7)	PROVISION FOR EARTHING		N
4.9 (7.2.1 + 7.2.3)	Accessible metal parts		N
	Metal parts in contact with supporting surface		N
	Resistance < 0,5 Ω..... :		N
	Self-tapping screws used		N
	Thread-forming screws		N
	Thread-forming screw used in a groove		N
	Earth makes contact first		N
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N
	Protective earthing of the luminaire not via built-in control gear		N
4.8 (7.2.2 + 7.2.3)	Earth continuity in joints, etc.		N
4.9 (7.2.4)	Locking of clamping means		N
	Compliance with 4.7.3		N
	Terminal blocks with integrated screwless earthing contacts tested according Annex V		N
4.9 (7.2.5)	Earth terminal integral part of connector socket		N
4.9 (7.2.6)	Earth terminal adjacent to mains terminals		N



4.9 (7.2.7)	Electrolytic corrosion of the earth terminal		N
4.9 (7.2.8)	Material of earth terminal		N
	Contact surface bare metal		N
4.9 (7.2.10)	Class II luminaire for looping-in		N
	Double or reinforced insulation to functional earth		N
4.9 (7.2.11)	Earthing core coloured green-yellow		N
	Length of earth conductor		N

4.10 (14)	SCREW TERMINALS		N
	Separately approved; component list	(see Annex 1)	N
	Part of the luminaire	(see Annex 3)	N

4.10 (15)	SCREWLESS TERMINALS AND ELECTRICAL CONNECTIONS		N
	Separately approved; component list	(see Annex 1)	N
	Part of the luminaire	(see Annex 4)	N

4.11 (5)	EXTERNAL AND INTERNAL WIRING		P
4.11 (5.2)	Supply connection and external wiring		P
4.11 (5.2.1)	Means of connection		N
	Outdoor luminaire has not PVC insulated external wiring if not class III or SELV ≤ 25 V a.c./60 V d.c. or protected from outdoor environment		N
4.11 (5.2.2)	Type of cable		P
	Nominal cross-sectional area (mm ²)	0.75 mm ²	P
	Cables equal to IEC 60227 or IEC 60245		P
4.11 (5.2.3)	Type of attachment, X, Y or Z	Y	P
4.11 (5.2.5)	Type Z not connected to screws		N
4.11 (5.2.6)	Cable entries:		P
	- suitable for introduction		P
	- adequate degree of protection		N
4.11 (5.2.7)	Cable entries through rigid material have rounded edges		P
4.11 (5.2.8)	Insulating bushings:		N
	- suitably fixed		N
	- material in bushings		N
	- material not likely to deteriorate		N



	- tubes or guards made of insulating material		N
4.11 (5.2.9)	Locking of screwed bushings		N
4.11 (5.2.10)	Cord anchorage:		N
	- covering protected from abrasion		N
	- clear how to be effective		N
	- no mechanical or thermal stress		N
	- no tying of cables into knots etc.		N
	- insulating material or lining		N
4.11 (5.2.10.1)	Cord anchorage for type X attachment:		N
	a) at least one part fixed		N
	b) types of cable		N
	c) no damaging of the cable		N
	d) whole cable can be mounted		N
	e) no touching of clamping screws		N
	f) metal screw not directly on cable		N
	g) replacement without special tool		N
	Glands not used as anchorage		N
	Labyrinth type anchorages		N
4.11 (5.2.10.2)	Adequate cord anchorage for type Y and type Z attachment	Y	P
4.11 (5.2.10.3)	Tests:		N
	- impossible to push cable; unsafe		N
	- pull test: 25 times; pull (N).....:		N
	- torque test: torque (Nm).....:		N
	- displacement ≤ 2 mm		N
	- no movement of conductors		N
	- no damage of cable or cord		N
	- function independent of electrical connection		N
4.11 (5.2.11)	External wiring passing into luminaire		P
4.11 (5.2.12)	Looping-in terminals		N
4.11 (5.2.13)	Wire ends not tinned		N
	Wire ends tinned: no cold flow		N



4.11 (5.2.14)	Mains plug same protection		P
	Class III luminaire plug		P
	No unsafe compatibility		P
4.11 (5.2.15)	Colour code low voltage		N
4.11 (5.2.16)	Appliance inlets (IEC 60320)		N
	Installation couplers (IEC 61535)		N
	Other appliance inlet or connector according relevant IEC standard		N
4.11 (5.2.17)	No standardized interconnecting cables properly assembled		N
4.11 (5.2.18)	Used plug in accordance with		P
	- IEC 60083		P
	- other standard		N
4.11 (5.3)	Internal wiring		P
4.11 (5.3.1)	Internal wiring of suitable size and type		P
	Through wiring		N
	- not delivered/ mounting instruction		N
	- factory assembled		N
	- socket outlet loaded (A)..... :		N
	- temperatures : (see Annex 2)		N
	Green-yellow for earth only		N
4.11 (5.3.1.1)	Internal wiring connected directly to fixed wiring		P
	Cross-sectional area (mm ²)..... :		P
	Insulation thickness		P
	Extra insulation added where necessary		N
4.11 (5.3.1.2)	Internal wiring connected to fixed wiring via internal current-limiting device		N
	Adequate cross-sectional area and insulation thickness		N
4.11 (5.3.1.3)	Double or reinforced insulation for class II		N
4.11 (5.3.1.4)	Conductors without insulation		N
4.11 (5.3.1.5)	SELV current-carrying parts		P



4.11 (5.3.1.6)	Insulation thickness other than PVC or rubber		P
4.11 (5.3.2)	Sharp edges etc.		P
	No moving parts of switches etc.		P
	Joints, raising/lowering devices		N
	Telescopic tubes etc.		N
	No twisting over 360°		N
4.11 (5.3.3)	Insulating bushings:		N
	- suitable fixed		N
	- material in bushings		N
	- material not likely to deteriorate		N
	- cables with protective sheath		N
4.11 (5.3.4)	Joints and junctions effectively insulated		N
4.11 (5.3.5)	Strain on internal wiring		P
4.11 (5.3.6)	Wire carriers		N
4.11 (5.3.7)	Wire ends not tinned		N
	Wire ends tinned: no cold flow		N
4.11.1 (-)	Indoor use luminaire The requirement of one part of cord anchorage to be fixed to the luminaire not applied for table lamps of glass or ceramic		
4.11.2 (-)	Class I and class II indoor use Luminaire with a mass less than 1 kg the current $\leq 2,5$ A and cable ≤ 2 m and conductor $\geq 0,5$ mm ²		
4.11.3 (-)	Portable luminaire for outdoor use delivered without a flexible cable or cord and a plug		
	Terminals, a cord anchorage and an inlet opening for the proper connection of the flexible cable or cord.		
4.11.4 (-)	Portable luminaires for outdoor use Insulation class I and class II, non-detachable flexible cables or cords at least type 245 IEC 57.		

4.12 (8)	PROTECTION AGAINST ELECTRIC SHOCK		P
4.12 (8.2.1)	Live parts not accessible		P
	Basic insulated parts not used on the outer surface without appropriate protection		P
	Basic insulated parts not accessible with standard test finger on portable, settable and adjustable luminaires		N
	Basic insulated parts not accessible with Ø 50 mm probe from outside, other types of luminaires		P



	Lamp and starterholders in portable and adjustable luminaires comply with double or reinforced insulation requirements		N
	Basic insulation only accessible under lamp or starter replacement		N
	Protection in any position		N
	Double-ended tungsten filament lamp		N
	Insulation lacquer not reliable		N
	Double-ended high pressure discharge lamp		N
	Relevant warning according to 3.2.18 fitted to the luminaire		P
4.12 (8.2.2)	Portable luminaire adjusted in most unfavourable position		P
4.12 (8.2.3.a)	Class II luminaire:		N
	- basic insulated metal parts not accessible during starter or lamp replacement		N
	- basic insulation not accessible other than during starter or lamp replacement		N
	- glass protective shields not used as supplementary insulation		N
4.12 (8.2.3.b)	BC lampholder of metal in class I luminaires shall be earthed		N
4.12 (8.2.3.c)	SELV circuits with exposed current carrying parts:		P
	Ordinary luminaire:		P
	- voltage under load (V)	<60 V	P
	- no-load voltage (V)	<60 V	P
	- touch current if applicable (mA)	<2.0 mA	P
	One conductive part insulated if required		N
	Other than ordinary luminaire:		N
	- nominal voltage (V)		N
	Class III luminaire only for connection to SELV		N
	Class III luminaire not provided with means for protective earthing		N
4.12 (8.2.4)	Portable luminaire have protection independent of supporting surface		P
4.12 (8.2.5)	Compliance with the standard test finger or relevant probe		P
4.12 (8.2.6)	Covers reliably secured		N



4.12 (8.2.7)	Luminaire other than below with capacitor > 0,5 μ F not exceed 50 V 1 min after disconnection		N
	Portable luminaire with capacitor > 0,1 μ F (0.25) not exceed 34 V 1 s after disconnection		N
	Other luminaires with capacitor > 0,1 μ F (0.25) with plug and track adaptors not exceed 60 V 5 s after disconnection		N
4.12.1 (-)	Class I luminaire with bayonet lampholder:		N
	1) cap not accessible with test finger		N
	2) metal lampholder is earthed		N

4.13 (12)	ENDURANCE TEST AND THERMAL TEST		P
4.13 (-)	If IP > IP 20 relevant test of (12.4), (12.5) and (12.6) after (9.2) before (9.3) specified in 1.13		—
4.13 (12.3)	Endurance test:		P
	- mounting-position	Normal position	—
	- test temperature (°C).....	35°C	—
	- total duration (h)	240h	—
	- supply voltage: Un factor; calculated voltage (V) ...:	3.7x1.1=4.07V	—
	- lamp used	LED	—
4.13 (12.3.2)	After endurance test:		P
	- no part unserviceable		P
	- luminaire not unsafe		P
	- no damage to track system		N
	- marking legible		P
	- no cracks, deformation etc.		P
4.13 (12.4)	Thermal test (normal operation)	(see Annex 2)	P
4.13 (12.5)	Thermal test (abnormal operation)	(see Annex 2)	N
4.13 (12.6)	Thermal test (failed lamp control gear condition):		N
4.13 (12.6.1)	Through wiring or looping-in wiring loaded by a current of (A)		—
	- case of abnormal conditions		—
	- electronic lamp control gear		
	- measured winding temperature (°C): at 1,1 Un		—
	- measured mounting surface temperature (°C) at 1,1 Un		N
	- calculated mounting surface temperature (°C)		N



	- track-mounted luminaires		N
4.13 (12.6.2)	Temperature sensing control		N
	- case of abnormal conditions		—
	- thermal link		N
	- manual reset cut-out		N
	- auto reset cut-out		N
	- measured mounting surface temperature (°C).....		N
	- track-mounted luminaires		N
4.13 (12.7)	Thermal test (failed lamp control gear in plastic luminaires):		N
4.13 (12.7.1)	Luminaire without temperature sensing control		N
4.13 (12.7.1.1)	Luminaire with fluorescent lamp ≤ 70W		N
	Test method 12.7.1.1 or Annex W		—
	Test according to 12.7.1.1:		N
	- case of abnormal conditions		—
	- Ballast failure at supply voltage (V)		—
	- Components retained in place after the test		N
	- Test with standard test finger after the test		N
	Test according to Annex W:		N
	- case of abnormal conditions		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C)		—
	Ball-pressure test.....		N
4.13 (12.7.1.2)	Luminaire with discharge lamp, fluorescent lamp > 70W, transformer > 10 VA		N
	- case of abnormal conditions		—
	- measured winding temperature (°C): at 1,1 Un.....		—
	- measured temperature of fixing point/exposed part (°C): at 1,1 Un.....		—
	- calculated temperature of fixing point/exposed part (°C)		—
	Ball-pressure test.....		N



4.13 (12.7.1.3)	Luminaire with short circuit proof transformers ≤ 10 VA		N
	- case of abnormal conditions		—
	- Components retained in place after the test		N
	- Test with standard test finger after the test		N
4.13 (12.7.2)	Luminaire with temperature sensing control		N
	- thermal link	Yes ☐ No ☐	—
	- manual reset cut-out.....	Yes ☐ No ☐	—
	- auto reset cut-out	Yes ☐ No ☐	—
	- case of abnormal conditions		—
	- highest measured temperature of fixing point/ exposed part (°C):		—
	Ball-pressure test:.....	See Table 4.15 (13.2.1)	N
4.13 (-)	Indoor use luminaire, Test overturned position (overturns < 15°)		

4.14 (9)	RESISTANCE TO DUST AND MOISTURE		P
4.14 (-)	If IP > IP 20 the order of tests as specified in clause 4.12		N
4.14 (9.2)	Tests for ingress of dust, solid objects and moisture:		N
	- classification according to IP	IP20	—
	- mounting position during test		—
	- fixing screws tightened; torque (Nm).....		—
	- tests according to clauses		—
	- electric strength test afterwards		N
	a) no deposit in dust-proof luminaire		N
	b) no talcum in dust-tight luminaire		N
	c) no trace of water on current-carrying parts or on insulation where it could become a hazard		N
	c.1) For luminaires without drain holes – no water entry		N
	c.2) For luminaires with drain holes – no hazardous water entry		N
	d) no water in watertight or pressure watertight luminaire		N
	e) no contact with live parts (IP 2X)		N
	e) no entry into enclosure (IP 3X and IP 4X)		N
	e) no contact with live parts through drain holes and ventilation slots (IP3X and IP4X)		N



	f) no trace of water on part of lamp requiring protection from splashing water		N
	g) no damage of protective shield or glass envelope		N
4.14 (9.3)	Humidity test 48 h	R.H.: 95% T: 25°C	P
4-14 (-)	Portable luminaire for outdoor use tested in the most unfavourable of the overturned positions likely to occur		

4.15 (10)	INSULATION RESISTANCE AND ELECTRIC STRENGTH		P
4.15 (10.2.1)	Insulation resistance test		P
	Cable or cord covered by metal foil or replaced by a metal rod of mm Ø		—
	Insulation resistance (MΩ).....		—
	SELV		N
	- between current-carrying parts of different polarity :		N
	- between current-carrying parts and mounting surface		N
	- between current-carrying parts and metal parts of the luminaire		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N
	- Insulation bushings as described in Section 5		N
	Other than SELV		P
	- between live parts of different polarity	>100M Ω	P
	- between live parts and mounting surface.....	>100M Ω	P
	- between live parts and metal parts.....	>100M Ω	P
	- between live parts of different polarity through action of a switch.....		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts		N
	- Insulation bushings as described in Section 5		N
4.15 (10.2.2)	Electric strength test		P
	Dummy lamp		N
	Luminaires with ignitors after 24 h test		N
	Luminaires with manual ignitors		N
	Test voltage (V)		P



	SELV		N
	- between current-carrying parts of different polarity :		N
	- between current-carrying parts and mounting surface :		N
	- between current-carrying parts and metal parts of the luminaire :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts :		N
	- Insulation bushings as described in Section 5 :		N
	Other than SELV		P
	- between live parts of different polarity :	2960V, No broken	P
	- between live parts and mounting surface :	2960V, No broken	P
	- between live parts and metal parts :	2960V, No broken	P
	- between live parts of different polarity through action of a switch :		N
	- between the outer surface of a flexible cord or cable where it is clamped in a cord anchorage and accessible metal parts :		N
	- Insulation bushings as described in Section 5 :		N
4.15 (10.3)	Touch current or protective conductor current (mA):		N

4.16 (13)	RESISTANCE TO HEAT, FIRE AND TRACKING		P
4.16 (13.2.1)	Ball-pressure test..... :	See Test Table 4.15 (13.2.1)	P
4.16 (13.3.1)	Needle-flame test (10 s) :	See Test Table 4.15 (13.3.1)	P
4.16 (13.3.2)	Glow-wire test (650°C)..... :	See Test Table 4.15 (13.3.2)	P
4.16 (13.4)	Proof tracking test (IEC 60112) :	See Test Table 4.15 (13.4)	N



4.7 (11.2)	TABLE: Creepage distances and clearances							P
	Minimum distances (mm) for a.c. (50/60 Hz) sinusoidal voltages							
	Applicable part of IEC 60598-1 Table 11.1* and 11.2*							
	Insulation type **	Measured clearance	Required		Measured creepage	Required		
			clearance	*Table		creepage	*Table	
Distance 1:	B	>1.5	1.5	11.1	>2.5	2.5	11.2	
Working voltage (V)					3.7V		—	
PTI					< 600 ☐ ≥ 600 ☐		—	
Pulse voltage if applicable (kV)							—	
Supplementary information:								
Distance 2:	R	>3.0	3.0	11.1	>5.0	5.0	11.2	
Working voltage (V)					3.7V		—	
PTI					< 600 ☐ ≥ 600 ☐		—	
Pulse voltage if applicable (kV)							—	
Supplementary information:								
Distance 3:	R	>3.0	3.0	11.1	>5.0	5.0	11.2	
Working voltage (V)					3.7V		—	
PTI					< 600 ☐ ≥ 600 ☐		—	
Pulse voltage if applicable (kV)							—	
Supplementary information: ** Insulation type: B – Basic; S – Supplementary; R – Reinforced. See also IEC 60598-1 Annex M.								

4.15a (13.2.1)	TABLE: Ball Pressure Test of Thermoplastics			P
Allowed impression diameter (mm) :				—
Object/ Part No./ Material	Manufacturer/ trademark	Test temperature (°C)	Impression diameter (mm)	
Switch	/	125°C	0.8	
Supplementary information:				



4.15b (13.3.1)	TABLE: Needle-flame test (IEC 60695-11-5)				P
Object/ Part No./ Material	Manufacturer/ trademark	Duration of application of test flame (ta); (s)	Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Switch	/	30	No	/	
Supplementary information:					

4.15c (13.3.2)	TABLE: Glow-wire test (IEC 60695-2-11)				P
Glow wire temperature :		650°C			—
Object/ Part No./ Material	Manufacturer/ trademark		Ignition of specified layer Yes/No	Duration of burning (tb) (s)	Verdict
Switch	/		No	/	
Any flame or glowing of the sample extinguished within 30 s of withdrawing the glow-wire, and any burning or molten drop did not ignite the underlying parts (Yes/No)..... :					
Supplementary information:					

4.15d (13.4)	TABLE: Proof tracking test (IEC 60112)					N
Test voltage PTI :			175 V			—
Object/ Part No./ Material		Manufacturer/ trademark	Withstand 50 drops without failure on three places or on three specimens			Verdict
Supplementary information:						

ANNEX 1	TABLE: Critical components information					N
Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Standard	Mark(s) of conformity	

ANNEX 2	TABLE: Temperature measurements, thermal tests of Section 12				P
	Type reference :	See page 2			—



	Lamp used..... :	LED	—				
	Lamp control gear used..... :		—				
	Mounting position of luminaire..... :	Normal position	—				
	Supply wattage (W) :	5.18W	—				
	Supply current (A)..... :		—				
	Calculated power factor..... :		—				
	Table: measured temperatures corrected for ta = 25 °C:		P				
	- abnormal operating mode :		—				
	- test 1: rated voltage :		—				
	- test 2: 1,06 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current :	3.7V x1.06=3.922V	—				
	- test 3: Load on wiring to socket-outlet, 1,06 times voltage or 1,05 times wattage..... :		—				
	- test 4: 1,1 times rated voltage or 1,05 times rated wattage or 1,1 times constant voltage/current..... :		—				
	Through wiring or looping-in wiring loaded by a current of A during the test :		—				
Temperature measurements, (°C)							
Part	Ambient	Clause 12.4 – normal				Clause 12.5 – abnormal	
		test 1	test 2	test 3	limit	test 4	limit
Internal wire	25.0		41.3		105		
Enclosure	25.0		42.6		Ref		
Supplementary information:							

ANNEX 3	Screw terminals (part of the luminaire)	N
(14)	SCREW TERMINALS	N
(14.2)	Type of terminal	—
	Rated current (A)	—
(14.3.2.1)	One or more conductors	N
(14.3.2.2)	Special preparation	N
(14.3.2.3)	Terminal size	N
	Cross-sectional area (mm^2)	—
(14.3.3)	Conductor space (mm)	N
(14.4)	Mechanical tests	N
(14.4.1)	Minimum distance	N



(14.4.2)	Cannot slip out		N
(14.4.3)	Special preparation		N
(14.4.4)	Nominal diameter of thread (metric ISO thread)		N
	External wiring		N
	No soft metal		N
(14.4.5)	Corrosion		N
(14.4.6)	Nominal diameter of thread (mm)		N
	Torque (Nm)		N
(14.4.7)	Between metal surfaces		N
	Lug terminal		N
	Mantle terminal		N
	Pull test; pull (N)		N
(14.4.8)	Without undue damage		N

ANNEX 4	Screwless terminals (part of the luminaire)		N
(15)	SCREWLESS TERMINALS		N
(15.2)	Type of terminal		—
	Rated current (A)		—
(15.3.1)	Material		N
(15.3.2)	Clamping		N
(15.3.3)	Stop		N
(15.3.4)	Unprepared conductors		N
(15.3.5)	Pressure on insulating material		N
(15.3.6)	Clear connection method		N
(15.3.7)	Clamping independently		N
(15.3.8)	Fixed in position		N
(15.3.10)	Conductor size		N
	Type of conductor		N
(15.5)	Terminals and connections for internal wiring		N
(15.5.1)	Mechanical tests		N
(15.5.1.1.1)	Pull test spring-type terminals (4 N, 4 samples)		N
(15.5.1.1.2)	Pull test pin or tab terminals (4 N, 4 samples)		N
	Insertion force not exceeding 50 N		N
(15.5.1.2)	Permanent connections: pull-off test (20 N)		N
(15.5.2)	Electrical tests		N



	Voltage drop (mV) after 1 h (4 samples)		N
	Voltage drop of two inseparable joints		N
	Number of cycles:		—
	Voltage drop (mV) after 10th alt. 25th cycle (4 samples).....		N
	Voltage drop (mV) after 50th alt. 100th cycle (4 samples).....		N
	After ageing, voltage drop (mV) after 10th alt. 25th cycle (4 samples).....		N
	After ageing, voltage drop (mV) after 50th alt. 100th cycle (4 samples).....		N
(15.6)	Terminals and connections for external wiring		N
(15.6.1)	Conductors		N
	Terminal size and rating		N
15.6.2	Mechanical tests		N
(15.6.2.1)	Pull test spring-type terminals or welded connections (4 samples); pull (N)		N
(15.6.2.2)	Pull test pin or tab terminals (4 samples); pull (N)		N
(15.6.3)	Electrical tests		N
	Tests according 15.6.3.1 + 15.6.3.2 in IEC 60598-1		N

(15.6.3.1)	TABLE: Contact resistance test / Heating tests										N
(15.6.3.2)											
	Voltage drop (mV) after 1 h										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop of two inseparable joints										
	Voltage drop after 10th alt. 25th cycle										
	Max. allowed voltage drop (mV)..... :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV)..... :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 10th alt. 25th cycle										




	Max. allowed voltage drop (mV)..... :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
	Continued ageing: voltage drop after 50th alt. 100th cycle										
	Max. allowed voltage drop (mV)..... :										—
terminal	1	2	3	4	5	6	7	8	9	10	
voltage drop (mV)											
Supplementary information:											



ANNEX A:

Photo-documentation



EUT



EUT